

Estimate - Order G50

Yellow = Art. most used Orange = other Art.

The calculation table on the right is suitable for indicative calculations. Warning, the exact quantities are obtained only by designing the structure.		ml profile	25	Screws for alternated fixing N. -			
		Rubber fittings distance centre (cm)		Screw for double fixing N. -			
		Floorboard width (mm)		Rubber fittings N. -			
		Medium length floorboard (cm)		Profile of junction N. -			
		Sq m surface					
Art.	Description	UM	€	Quantity	Amount	Min. Quantity	Package
6358	SuperFix fixing glue 430 ml 20 pc/Pack	pcs	22,50		-		
6304	Template for floorboard fixing thickness 18-23 mm, width 112 mm, joint 7 mm	pcs	21,00		-		
6305	Template for floorboard fixing thickness 18-23 mm, width 136 mm, joint 8 mm	pcs	21,00		-		
6303	Template for floorboard fixing thickness 18-23 mm, width 89 mm, joint 6 mm	pcs	21,00		-		
6364	Template for floorboard fixing thickness 24-28 mm, width 112 mm, joint 7 mm	pcs	21,00		-		
6365	Template for floorboard fixing thickness 24-28 mm, width 136 mm, joint 8 mm	pcs	21,00		-		
6363	Template for floorboard fixing thickness 24-28 mm, width 89 mm, joint 6 mm	pcs	21,00		-		
6306	Template for universal adjustable floorboard fixing, thickness 18-23 mm, width 80/150 mm, joint 4,6,8 mm	pcs	54,00		-		
6366	Template for universal adjustable floorboard fixing, thickness 24-28 mm, width 80/150 mm, joint 4,6,8 mm	pcs	54,00		-		
6361	Badi board dimension. 1.800/3.000 x 100/150 x 25 mm. Non-slip profile. Not dried.	sq. m			-		
5898	Bangkirai board, dimension. 1.800/4.300 x 145 x 28 mm. Non-slip profile. Not dried.	sq. m	52,50		-		
6362	Ipe/Lapacho board, dimension. 1.800/3.000 x 100/150 x 25 mm. Non-slip profile. Not dried.	sq. m			-		
6280	Teack Burma, board dimension. 1.800/2.400 x 89 x 22 mm, non-slip profile and pedestrian heel proof, occasional knots are allowed.	sq. m			-		
6281	Teack Burma, board dimension. 1.800/2.400 x 112 x 22 mm, non-slip profile and pedestrian heel proof, occasional knots are acceptable.	sq. m			-		
6182	Thermowood D board in Beech, dimension 3.000 x 136 x 26 mm, top-edge gluing with EPI glue for external use (rain and sun ledger) non vinyl glue, non-slip profile and pedestrian heel proof, occasional knots are acceptable. 0.41 sq.m/pcs	sq. m	104,00		-		
6069	Thermowood D board in Beech, dimension 6.000 x 112 x 26 mm, top-edge gluing with EPI glue for external use (rain and sun ledger) non vinyl glue, non-slip profile and pedestrian heel proof, occasional knots are acceptable. 0.67 sq.m/pcs	sq. m	104,00		-		
6068	Thermowood D board in Beech, dimension 6.000 x 89 x 26 mm, top-edge gluing with EPI glue for external use (rain and sun ledger) non vinyl glue, non-slip profile and pedestrian heel proof, occasional knots are acceptable.	sq. m	104,00		-		
6279	Thermowood D board in Ash, dimension 1.500/3.000 x 112 x 25 mm, non-slip profile and pedestrian heel proof, occasional knots are acceptable.	sq. m	104,00		-		
6360	Thermowood D board in Ash, dimension 1.500/3.000 x 136 x 25 mm, non-slip profile and pedestrian heel proof, occasional knots are acceptable.	sq. m	104,00		-		
6359	Thermowood D board in Ash, dimension 1.500/3.000 x 89 x 25 mm, non-slip profile and pedestrian heel proof, occasional knots are acceptable.	sq. m	104,00		-		
6278	Thermowood D board in knotted Pine, dimension 2.100/3.600 x 112 x 25 mm, non-slip profile and pedestrian heel proof, frequent knots are acceptable.	sq. m	46,00		-		
5836	Rubber fittings in EPDM rubber, UV resistant and frost; 40 x 4 mm; 50 pcs/Pkt. ; 40 Pack/Box (min 1 Pack.)	pcs	0,18		-	-	50
6326	Profile support in aluminium, black (RAL 9005); section 20 x 20 x 3000 mm; 3 ml/pcs; 9 pcs/Pkt	ml	4,35		-	-	9
6329	Profile support for junctions in aluminium, black, pre-cut at 170 mm for boards of 89 mm 9 pcs/Pkt ; 28 Pkt/Box (min 1 Pkt)	pcs	1,00		-	-	9
6328	Profile support for junctions in aluminium, black, pre-cut at 195 mm for boards of 112 mm 9 pcs/Pkt ; 28 Pkt/Box (min 1 Pkt)	pcs	1,05		-	-	9
6327	Profile support for junctions in aluminium, black, pre-cut at 225 mm for boards of 136 mm 9 pcs/Pkt ; 28 Pkt/Box (min 1 Pkt)	pcs	1,20		-	-	27
5838	10/7 mm double diameter tip for hole plug on aluminium support profile	pcs	61,50		-	-	
5840	HSS steel pre-bore hole tip for Thermowood in Ash and Beech, Teack, Bangkirai, Ipe, Badi; 4,7 x 80 mm 10 pcs/Pkt. (min 1 Pkt.)	pcs	2,05		-	-	10
5842	HSS steel pre-bore hole tip for Thermowood in Pine 4,5 x 80 mm 10 pcs/Pkt. (min 1 Pkt.)	pcs	2,05		-	-	10
6299	Thickness 1 x 45 x 45 mm made in UV and frost resistant EPDM rubber 50 pcs/Pkt (min 1 Pkt.)	pcs	0,23		-	-	50
6300	Thickness 3 x 45 x 45 mm made in UV and frost resistant EPDM rubber 50 pcs/Pkt (min 1 Pkt.)	pcs	0,45		-	-	50
6301	Thickness 10 x 45 x 45 mm made in UV and frost resistant EPDM rubber 25 pcs/Pkt (min 1 Pkt.)	pcs	0,95		-	-	25
5837	Fastening plug for masonry in stainless steel A2 / AISI 304; 6 x 60 mm; 50 pcs/Pkt. (min 1 Pkt.)	pcs	0,60		-	-	50
6316	Double thread insert screw TX20; in stainless steel A2 / AISI 304, 5.5 x 34 mm, head sight diam. 6.5 mm. Pre-bore hole diameter for the G50 system, see instructions. 200 pcs / Pkt.	pcs	0,21		-	-	200
6315	Double thread insert screw TX20; in stainless steel A2 / AISI 304, 5.5 x 40 mm, head sight diam. 6.5 mm. Pre-bore hole diameter for the G50 system, see instructions. 200 pcs / Pkt.	pcs	0,21		-	-	200
Date:				Total €		-	
Client:				Discount %			
Add:				Discount subtotal		-	
Cons:				Total with discount		-	
Note:				VAT excluded			